

Title	Fermionic Implementation of PEPS algorithm(New Development of Numerical Simulations in Low-Dimensional Quantum Systems: From Density Matrix Renormalization Group to Tensor Network Formulations)
Author(s)	Pizorn, Iztok; Verstraete, Frank
Citation	物性研究 (2011), 95(6): 631-631
Issue Date	2011-03-05
URL	<a href="http://hdl.handle.net/2433/169437">http://hdl.handle.net/2433/169437</a>
Right	
Type	Departmental Bulletin Paper
Textversion	publisher

# Fermionic Implementation of PEPS algorithm

Iztok Pižorn and Frank Verstraete

Faculty of Physics, University of Vienna, Boltzmanngasse 5, A-1090 Wien, AUSTRIA

We present an efficient method to simulate finite size fermionic quantum systems by fermionic projected entangled pair states (PEPS) [1, 2], following the fact that the expectation value of an arbitrary parity-preserving operator can be calculated efficiently for a fermionic PEPS state. Using the variational principles we implement [3] the PEPS variational algorithm to simulate ground states in a sign-free way by absorbing all fermionic signs locally. The method is tested on a bi-linear fermionic model on a square lattice for sizes up to ten by ten where good relative accuracy is achieved. Qualitatively good results are also obtained for an interacting fermionic system.

## References

- [1] F. Verstraete and J. I. Cirac, arXiv: cond-mat/0407066.
- [2] C. V. Kraus, N. Schuch, F. Verstraete, and J. I. Cirac, Phys. Rev. A **81** (2010), 052338.
- [3] I. Pižorn and F. Verstraete, Phys. Rev. B **81** (2010), 245110.